

Pedestal Fans

by Hydor

The Pedestal Fan is available in stand or wall mounted configurations and is designed to provide fast, cool relief in many locations including marquees, club rooms, shops, restaurants, gymnasiums, schools, halls, workshops and warehouses.

Construction

Stand mounted version (SPF) fitted with heavy cast iron base.
 Wall mounted version (SWF) provided with wall mounting kit. Impellers are of aluminium and fully balanced.
 Wire guards of chrome plated mesh.
 All Steel components have a corrosion resistant finish.
 Supplied in Kit form for ease of assembly

Motor

Type - squirrel cage induction motor.
 Electrical supply - 220-240V, single phase, 50 Hz.
 3 speed motor.
 Bearings - sealed-for-life, ball.

Special Features

Powerful 635mm dia fan
 3 speed-and-off regulator fitted as standard.
 Stand mount version height adjustable up to 1500mm.
 Oscillation - 90° horizontal swing mechanism.
 Tilting mechanism for vertical adjustment.
 BEAB approved



Product Code	Duty m ³ /s			Weight kg
	LOW	MED	HIGH	
SPF63	2,6	3,0	3,3	25kg
SWF63	2,6	3,0	3,3	15kg
dBA @ 3m	55	59	68	
power Watts	135	150	175	
Current Amps	0,56	0,6	0,8	

